


# iDISPLAY™ Tablet 55" UIT455B



The iDISPLAY Tablet 55" is designed as an freestanding or wall based interactive display. Operating on an Android operating system and powered by Pulse technology, this slim and elegant display includes all of the solutions needed for commercial locations. Attach to any standard TV/monitor VESA bracket and simply turn on the power. It is a fully interactive commercial display that uses capacitive touch, built in WiFi and LAN, and a host of integrated features that work in either landscape or portrait format. With the option to expand to 3G services\*, this is an amazing, large screen interactive digital display that creates an engaging, memorable consumer experience.



\*3G optional, pending carrier compatibility/availability.  
For more information about iDISPLAY™ Tablets  
please visit our website: [www.outform.com/iDisplay-Tablets](http://www.outform.com/iDisplay-Tablets)

Panel Information	Screen Size	55"
	Resolution	1920 x 1080 Pixels
	Brightness	350 cd/m <sup>2</sup>
	Contrast Ratio	4000
	Aspect Ratio	16:9
	Active Area Size (WxH)	1207.60 x 678.40mm
	Viewing Angle Touch	89°/89°(H), 89°/89°(V)
	Touch Technology	Capacitive G+G 10 point
Hardware and OS	CPU	RK3288, Cortex-A17, up to 1.8GHz Quad Core
	GPU	Mali T764
	Internal Memory	2GB, DDR3
	Flash Memory	16GB
	Operating System	Android 4.4 / 5.1
	Battery	N/A
Video/Images	Video Formats	3GP, MP4, AVI, MKV, FLV, MOV
	Video Codecs	MPG-1, MPG-2, MPG-4, H.263, H.264, VC-1, RV, VP6/VP8, MVC
	Image Formats	JPG/JPEG, PNG, BMP
	HDMI Output	Yes
	Playback Software	Built-in software allows for easy setup of a playlist of videos and/or stills which can be looped infinitely without any additional software. Alternatively, any installed app can be auto-started upon boot-up.
Audio	Speakers	5W x 2
	Audio Codecs	MP3, WMA, AAC, FLAC, WAV
Communications	Bluetooth	4.0
	Wi-Fi	802.11 b/g/n 2.4GHz
	Wired Ethernet	10M/100M
	Wireless 3G	Through external USB dongle (optional)
General information	Color	Black (Standard), White (Optional)
	Camera	N/A
	I/O ports	SD, 3.5mm Audio Output Jack, USB 2.0 OTG x 1, USB 2.0 HOST x 2, HDMI, DC
	Included in Box	Display Unit, Power Cable, User Manual, Warranty
	Optional Accessories	N/A
	Sensors	G-Sensor (3-Axis accelerometer)
	Power Input	AC100-240V
	Power Consumption	120W (max)
	Power Over Ethernet	N/A
	Operating Temperature	0-50 °C
	Relative Humidity	85%
	Certification	Display Unit: ROHS, FCC and CE complaint Power Supply Unit: UL, FCC and CE compliant
Dimensions	Size (L x W x H)	1263.18 x 747.28 x 56.5mm
	Product Weight	31.6kg
	Gift Box Size	N/A
	Master Carton Size	1435 x 1020 x 175mm
	Master Carton Weight	40.2kg
	Units per Master Carton	1pcs